



- Ground cord used to connect mats to EBP (Earth Bonding Point) plugs
- 1 megohms (1x10E6 ohms) resistor in socket end
- 2.5mm cord diameter
- Several lengths available
- PVC insulation with 7 ends duplex tinsel copper conductor

ITEM	CODE	DESCRIPTION
230465	J4905	Cord, Straight, 0.25m, 10mm Socket, 4mm Plug
230490	J4921	Cord, Straight, 0.7m, 10mm Socket, 4mm Plug
230385	J4621	Cord, Straight, 1.5m, 10mm Socket, 4mm Plug
230415	J4721	Cord, Straight, 2.5m, 10mm Socket, 4mm Plug

"EPA ground cords shall be used to make electrical connections between groundable points and the EPA ground facility.

Where a single resistor is used in the EPA ground cord, this shall be located near the groundable point. Where more than one resistor is used, a resistor of a minimum resistance value of one half the total resistance shall be located near the groundable point.

When accessible, the EPA ground cord and its groundable point connection shall be shrouded by insulating material." (EN 61340-5-1 section 5.3.4 EPA ground cords)

Unless otherwise noted, tolerance is $\pm 10\%$

Specifications and procedures subject to change without notice.



Made in Britain

Vermason

Straight Cord, 10mm Socket, 4mm Plug

VERMASON
 UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH,
 HERTS, SG6 2TD UK
 PHONE: +44 (0) 1462-672005, FAX: +44 (0) 1462-670440
 E-MAIL: Service@Vermason.co.uk, INTERNET: Vermason.co.uk

Drawing Number
 230465

DATE:
 August
 2012