	Caution This bag contains MOISTURE-SENSITIVE DEV	VICES LEVEL
< 90% re	ed shelf life in sealed bag: 12 mo	bar code labe onths at < 40°C and
2. Peak pac	ckage body temperature:	e adjacent bar code label
	is opened, devices that will be so other high temperature process	
≤ 30°C	ed within:	of factory condition
a) Humid device	require bake, before mounting, it ity lidicator Card reads > 10% f s or > 60% for level 2 devices wi Bb not met	or level 2a - 5a
5. If baking bake pro	is required, refer to IPC/JEDEC cedure	J-STD-033 for
Bag Seal D	If blank, see adjacent ba	
Note: Lev	el and body emperature defined by IPO	C/JEDEC J-STD-020
06736 / 91309	\ /	Descolndustries.co

Moisture Warning Symbol and message clearly shown on label.

Item	Description	Qty/Roll
242201	82mm x 95mm, Permanent	100

COLOR: White with blue printing

SYMBOL: JEDEC J-STD-033B

PACKAGED: 100 per roll, 7.62 cm diameter core

DESCRIPTION: The product is designed for dry packing applications; the label provides the moisture warning symbol and displays a warning message needed to complete your dry package system. The label is tamper evident, allowing you to easily monitor whether or not the MBB has been opened. The permanent adhesive label is designed for use on all <u>Vermason Statshield® Moisture Barrier Bags</u> that are used in the dry packing of SMD tape and reel, guad flat pack/JEDEC trays, and component shipping tubes.

PRODUCT SPECIFICATIONS:

Adhesive: B-82, strong and permanent

Liner: 40# white Kraft
Facestock: 60# SemiGloss Litho

Service Temperature: -23 to +82°C

Minimum Labelling Temperature: -9°C

INK & VARNISH SPECIFICATIONS:

Water Resistance: Excellent
Grease Resistance: Excellent
Alcohol Resistance: Excellent
UV Resistance: Excellent

FEATURES

- 100 labels per roll
- · White label with blue printing
- · Coated with an ultra violet varnish for added durability
- · Strong, permanent adhesive
- Labels are mounted on a 7.62 cm core for use in tape dispensers
- Tamper evident

Vermason

LABEL, MOISTURE SENSITIVE, CAUTION, JEDEC J-STD-033B

VERMASON UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH, HERTS, SG6 2TD UK

PHONE: +44 (0) 1462-672005

E-MAIL: Service@Vermason.co.uk, INTERNET: Vermason.co.uk

Drawing Number 242201

DATE:December 2013